


## CL 110/CLPB 110 LN<sub>2</sub>, LOX, LARG Container

- · Ideal for conventional straight liquid dispensing
- Sizes range from 15 L to 500 L
- · Convenient fill/withdrawal valve
- · Vent valve with full tricock prevents overfilling
- · Pressure gauge and relief devices for safety
- Reliable, easy-to-read differential pressure-type liquid level gauge
- · Casters for easy mobility
- CLPB series adds a self-pressurizing system for convenience and transfer efficiency
- CLPB series feature adjustable regulator to maintain 10-25 PSI
- · Both series can be customized to fit your specific needs

	CL	CLPB	
Net Liter Capacity	110 L	110 L	
Gross Liter Capacity	121 L	121 L	
Outside Diameter	20"	20"	
Height	51"	51"	
Empy Weight	173 lbs	177 lbs	
Weight Full LN <sub>2</sub>	373 lbs	377 lbs	
Weight Full LOX	454 lbs	458 lbs	
Weight Full LARG	507 lbs	511 lbs	
N.E.R. (Normal Evaporation Rate)	2 L/day	2 L/day	
M.A.W.P. (Maximum Allowable Working Pressure)	25 PSI	25 PSI	
Regulator Setting	N/A	20	
Secondary Relief	100 PSI	100 PSI	
Caster Size	4"	4"	
Level Gauge	Yes	Yes	
Liquid Flow@22 PSI	-	-TBD-	
Liquid Fitting	-CGA 295 1	-CGA 295 1/2" 45° Male Flare-	
Vent Fitting	- 3	— 3/8" NPT—	
Material of Construction	-304 Grad	-304 Grade Stainless Steel-	



Symbol	Description
V-1	Liquid Fill/Withdrawal
V-2	Fill/Wlithdrawal Valve
V-3	Pressure Building
V-4	Vent Valve
RD-1	Rupture Disk
RV-1	Relief Device
Pg-1	Pressure Guage
LG-1	Liquid Level Buliding
PCV-1	Pressure Building Regulator
PBC-1	Pressure Building Coil

## **Available Options:**





**More Sizes** 

**Available** 















- · Removable Manifold
- · Gravity Feed Port
- Electric Pressure Builder
- · Dedicated Solenoid Port
- Top Vertical Withdrawal
- Additional Fill or Withdrawal Port
- Outboard Wheel Casters
- Pedal Locking Casters
- Wing Nut Locking Casters