


## CL 500/CLPB 500 LN<sub>2</sub>, LOX, LARG Container

- · Ideal for conventional straight liquid dispensing
- Sizes range from 15 L to 500 L
- · Convenient fill/withdrawal valve
- · Vent valve with full tricock prevents overfilling
- Pressure gauge and relief devices for safety
- Reliable, easy-to-read differential pressure-type liquid level gauge
- · Casters for easy mobility
- CLPB series adds a self-pressurizing system for convenience and transfer efficiency
- CLPB series feature adjustable regulator to maintain 10-25 PSI
- Both series can be customized to fit your specific needs

	CL	CLPB
Net Liter Capacity	500 L	500 L
Gross Liter Capacity	550 L	550 L
Outside Diameter	32"	32"
Height	72"	72"
Empy Weight	660 lbs	668 lbs
Weight Full LN <sub>2</sub>	1558 lbs	1666 lbs
Weight Full LOX	1927 lbs	1935 lbs
Weight Full LARG	2168 lbs	2176 lbs
N.E.R. (Normal Evaporation Rate)	5 L/day	5 L/day
M.A.W.P. (Maximum Allowable Working Pressure)	25 PSI	25 PSI
Regulator Setting	N/A	20
Secondary Relief	100 PSI	100 PSI
Caster Size	5"	5"
Level Gauge	Yes	Yes
Liquid Flow@22 PSI	-TBD-	
Liquid Fitting	-CGA 295 1/2" 45° Male Flare-	
Vent Fitting	-3/8" NPT-	
Material of Construction	-304 Grade Stainless Steel-	



Symbol	Description
V-1	Liquid Fill/Withdrawal
V-2	Fill/Wlithdrawal Valve
V-3	Pressure Building
V-4	Vent Valve
RD-1	Rupture Disk
RV-1	Relief Device
Pg-1	Pressure Guage
LG-1	Liquid Level Buliding
PCV-1	Pressure Building Regulator
PBC-1	Pressure Building Coil

## **Available Options:**



- Removable Manifold
- Gravity Feed Port
- Electric Pressure Builder
- Dedicated Solenoid Port
- Top Vertical Withdrawal

**More Sizes** 

**Available** 

- Additional Fill or Withdrawal Port
- Wing Nut Locking Casters